



JC400P

Integrated Dual-Channel DashCam

With a highly integrated design, JC400P 4G dashcam comes with a 1080P front camera and a 720P on-device sub camera to record everything on the road and in the cabin. Furthermore, the 4G capability of the device enables seamless video streaming, live audio alerts, route replay, and video history playback. With all of these features, fleet managers can coach drivers based on data and improve operations to unlock more benefits, whether they're managing government, logistics, ride-hailing, or taxi fleets.



Video Surveillance

Powerful LTE connectivity enables the live monitoring of the vehicle's interior and exterior via an online platform; while the critical video clips in the device allows for on-demand playback after the fact from anywhere, at any time.



Dual-Channel Recording

Simultaneously monitor the road ahead and what happens in the cab in real-time through the two on-device lenses, with no peripheral camera needed.



Multiple Alerts

Record and upload video clips or still images of customizable events such as speeding and SOS button activation.



Compact Size

The small form factor allows discreet installation behind the rearview mirror without blocking the driver's view.



Vehicle Immobilization

Enable you to cut off the fuel/power to the vehicle moving under 20km/h using Tracksolid Pro, which is useful if your fleet vehicle has been stolen.




Fast Integration

We can provide an IoT Hub to facilitate fast and seamless integration to any third-party platform or the intelligent transport system (ITS).

Taxi service



Online Ride-hailing



Logistics Service



Hazmat Trucking



Specification

Network

Standard	4G LTE Cat.4
Wifi	2.4GHz, Support AP Mode/STD Mode/WIFI Direct
Bluetooth	BLE 4.0
Band	Eurasian Version LTE-FDD: B1/B3/B5/B7/B8/B19/B20 LTE-TDD: B38/B39/B40/B41 (100M) WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8
	American Version LTE-FDD: B2/B3/B4/B5/B7/B12/B17 LTE-TDD: B38/B41 (100M) WCDMA: B2/B4/B5 GSM: B2/B5/B8

Camera

Front Camera (Main)	1920x1080/25FPS/F2.2/Full color/118° (HfOV)
Sub Camera	1280x720/15FPS/F2.5/Full color in daytime & monochrome in dim light/90° (HfOV)
Video Format	.mp4

Configuration

GNSS	GPS/BDS
Sensor	6-axis
Microphone	Support
Speaker	Support
Interface	Micro USB*1, SOS*1, RS232*1, Relay*1
Memory Support	TF card (Up to 256GB)
SIM Card Type	Nano
LED Indication	Red (Power), Blue (Cellular), Green (GNSS)

Others

Power Supply	Power cable: B+/ACC/GND
Operating Voltage	DC 9~30V
Operating Temperature	-20°C to +65°C
Storage Temperature	-30°C to +85°C
Device Weight	233g
Device Dimension	109*69*52mm
Certifications	CE/FCC/RoHS